

# TRUCK TIRES



**DELIVERING PERFORMANCE  
DRIVING GROWTH**



**STEERING AXLE**

BRS1/BL221/BL223

4/5

**DRIVE AXLE**

BRD1/BL831/BL833/BL835/BL836

5/6/7

**TRAILER AXLE**

BRT1/BLT11/BLT16/BLT17/BL615

8/9/10

**ALL POSITION AXLES**


BL225/BLT15

10/11

## BRS1 REGIONAL

STEERING AXLE

- ✓ Innovative "SOCT" technology provides support on excellent mileage and handling performance
- ✓ Variable depth of sipes helps to ensure even wear of tread and good wet braking performance
- ✓ "Gemstone" groove help to prevent stone trapping and puncture to enhance casing toughness




Size	PLY	L/S	Rim	RR	WG	Noise	dB	3PMSF /M+S	Tread Depth (mm)
295/60R22.5	16PR	150/147L	9.00	D	B	B	72	3PMSF	12.5
315/60R22.5	18PR	154/150L(152/148M)	9.75	D	B	B	72	3PMSF	12.5
315/70R22.5	18PR	156/150L(154/150M)	9.00	C	B	B	72	3PMSF	14.5
315/80R22.5	22PR	158/150L(154/150M)	9.00	C	B	B	72	3PMSF	15.0

## BL221 REGIONAL

STEERING AXLE

- ✓ Suitable for steer and trailer axle of trucks running with high speed on highway
- ✓ Low rolling resistance, reducing fuel consumption
- ✓ Lasting grip and stability by hidden groove design
- ✓ New pattern design, improving mileage for long distance transportation




Size	PLY	L/S	Rim	RR	WG	Noise	dB	3PMSF /M+S	Tread Depth (mm)
295/60R22.5	16PR	150/147L	9.00	D	C	A	70	3PMSF	13.0
295/80R22.5	18PR	154/149M	9.00	D	C	A	70	3PMSF	14.0
315/60R22.5	16PR	152/148L	9.75	D	C	A	70	3PMSF	12.5
315/70R22.5	18PR	156/150L(154/150M)	9.00	D	C	A	70	3PMSF	15.0
385/55R22.5	20PR	160K(158L)	12.25	D	C	A	70	3PMSF	12.0

## BL223 REGIONAL

### STEERING AXLE

- ✓ Suitable for steer and trailer axle of trucks running under a wide range of use, from highway to light unpaved road
- ✓ Optimization of the shoulder block, improving resistance to shoulder damage
- ✓ Lasting grip and stability, with stone rejection design
- ✓ High wear resistance




Size	PLY	L/S	Rim	RR	WG	Noise	dB	3PMSF /M+S	Tread Depth (mm)
295/60R22.5	16PR	150/147L	9.00	D	C	A	69	3PMSF	14.0
295/80R22.5	18PR	154/149M	9.00	D	C	A	69	3PMSF	16.5
315/60R22.5	16PR	152/148L	9.75	D	C	A	69	3PMSF	12.5
315/70R22.5	18PR	156/150L(154/150M)	9.00	D	C	A	69	3PMSF	15.5
315/80R22.5	22PR	158/150L(154/150M)	9.00	D	C	A	69	3PMSF	15.5
385/55R22.5	20PR	160K(158L)	12.25	D	C	A	69	3PMSF	13.5
385/65R22.5	24PR	164K(158L)	11.75	D	C	A	69	3PMSF	15.5

## BRD1 REGIONAL

### DRIVE AXLE

- ✓ Innovative "SOCT" technology provides support on excellent mileage and handling performance
- ✓ 3D interlocking technology helps to control the movement of the tread blocks to avoid abnormal block wear
- ✓ Variable depth of sipes helps to ensure even wear of tread and good wet braking performance



Size	PLY	L/S	Rim	RR	WG	Noise	dB	3PMSF /M+S	Tread Depth (mm)
295/60R22.5	16PR	150/147L	9.00	E	B	C	75	3PMSF	17.0
315/60R22.5	16PR	152/148M	9.75	E	B	C	75	3PMSF	18.5
315/70R22.5	16PR	154/150L(152/148M)	9.00	E	B	C	75	3PMSF	19.5
315/80R22.5	20PR	156/150L(154/150M)	9.00	E	B	C	75	3PMSF	20.5